


Intara RD 197

LED BatWing

LIGHTING TECHNOLOGY

Design	Array
Light colour	2,700 . 3,000 . 4,000 K
Utilised flux	5,325 . 5,500 . 5,925 lm
System power	84 W
Reflector	BatWing
Beam angle	2 x 35°
Reflector colours	Silver



LUMINAIRE

Pivot angle	175°
Angle of adjustment	2 x 25°
Weight without driver unit	1.3 kg
Protection rating . Protection class	IP 20 . I
Luminaire colours	■ ■ □

Recessed luminaire for LED arrays, active cooling, reflector with double asymmetrical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, infinitely adjustable and pivotable, sheet steel mounting frame and luminaire housing, powder-coated, separate driver unit 220-240 V, 50/60 Hz

Including driver unit (765LEDSH84) and feed-through wiring set


Note: Due to further developments in the field of LED technology, the system power may be reduced within the framework of product upgrades

ORDER NUMBER

	■	■	□
2,700 K	5025 0007	5025 0008	5025 0009
3,000 K	5025 0001	5025 0003	5025 0005
4,000 K	5025 0002	5025 0004	5025 0006

OPTIONAL

RAL colours
Mounting accessories





Intara RD 197

LED WallBeam

LIGHTING TECHNOLOGY

Design	Array
Light colour	2,700 . 3,000 . 4,000 K
Utilised flux	5,075 . 5,250 . 5,650 lm
System power	84 W
Reflector	WallBeam
Beam angle	
Reflector colours	Silver



LUMINAIRE

Pivot angle	175°
Angle of adjustment	2 x 25°
Weight without driver unit	1,4 kg
Protection rating . Protection class	IP 20 . I
Luminaire colours	■ ■ □

Recessed luminaire for LED arrays, active cooling, reflector with asymmetrical light distribution pattern, 99.99% pure aluminium reflector made of MIRO-SILVER®, infinitely adjustable and pivotable, sheet steel mounting frame and luminaire housing, powder-coated, separate driver unit 220-240 V, 50/60Hz

Including driver unit (765LEDSH84) and feed-through wiring set

Note: Due to further developments in the field of LED technology, the system power may be reduced within the framework of product upgrades

ORDER NUMBER

	■	■	□
2,700 K	5024 0007	5024 0008	5024 0009
3,000 K	5024 0001	5024 0003	5024 0005
4,000 K	5024 0002	5024 0004	5024 0006

OPTIONAL

RAL colours
Mounting accessories

